

**COMMUNICATING PROGRAM IDENTIFIERS FROM A DIGITAL VIDEO
RECORDER (DVR) TO A SET TOP BOX (STB) INDEPENDENT OF WHEN THE STB
DEMODULATES THE ASSOCIATED PROGRAM DATA**

Cross Reference to Related Applications and Patents

This application is related to co-pending U.S. patent application serial no. 09/652,730 filed on 08/31/200 entitled "ELECTRONIC PROGRAM GUIDE SUBSYSTEM FOR RECEIVING AND PROCESSING ELECTRONIC PROGRAM GUIDE INFORMATION FROM A SET- TOP BOX", the disclosure of which is herein incorporated by reference.

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to digital video recorders. More particularly, the present invention relates to communicating program identifiers from a digital video recorder (DVR) to a set top box (STB) independent of when the STB demodulates the associated program data.

Description of the Prior Art

FIG. 1A shows a prior art digital video recorder or DVR 2 installed between a set top box or STB 4 (e.g., a tuner for digital cable) and a monitor 6. The STB 4 demodulates a selected channel from a program signal 5 and provides an audio and video (A/V) signal 7 to the DVR 2. The DVR 2 may record the A/V signal 7 for playback at a later time, or pass the A/V signal 7 through to the monitor 6 as A/V signal 9. The DVR 2 further comprises a modem for receiving Electronic Program Guide (EPG) data over a telephone line 8. The user operates a remote control 10 to direct the DVR 2 to display the EPG data on the monitor 6 in a DVR graphical user interface (GUI). The user can peruse the EPG data in the DVR GUI to select various programs to view and/or record.

The remote control 10 is also used to control the operation of the STB 4; that is, the remote control 10 of the DVR 2 is intended to replace the remote control of the STB 4. Commands are sent from the DVR 2 to the STB 4 over a control line 12. For example, if the user

1 selects a new channel with the remote control 10, the DVR 2 commands the STB 4 to tune to the
2 selected channel. In another example, if a program the user previously selected for recording
3 begins to air, the DVR 2 directs the STB 4 to tune to the appropriate channel.

4 Multiple System Operators (MSOs), such as AT&T digital cable, as well as other
5 broadband providers may not want the DVR 2 to commandeer the user interface. Broadband
6 providers may want to retain their format for displaying the EPG data in order to minimize the
7 burden on their viewers when a DVR is added to their system. Further, broadband providers
8 derive revenue through advertising information displayed with the EPG data, and prior art DVR
9 systems that replace the user interface may diminish the advertising revenue derived by the
10 broadband provider.

11 There is, therefore, a need for a DVR compatible with existing STB hardware that can
12 also accommodate the existing STB GUI.

13 SUMMARY OF THE INVENTION

14 The present invention may be regarded as a digital video recorder (DVR) for use with a
15 monitor and a set top box (STB), the STB for demodulating program data from a program signal
16 received over a communication channel and for generating a STB graphical user interface (GUI).
17 The STB further comprises a DVR interface. The DVR comprises a local memory for storing the
18 program data received from the STB, a plurality of program identifiers, and a STB interface for
19 communicating with the STB over the DVR interface. The DVR further comprises a DVR
20 controller for maintaining the plurality of program identifiers, and for communicating to the STB
21 the plurality of program identifiers independent of when the STB demodulates the program data
22 identified by the program identifiers. The STB is responsive to the plurality of program identifiers
23 to modify at least one selected operation of the STB.

24 In one embodiment, the plurality of program identifiers identify respective programs
25 scheduled for recording by the DVR. In another embodiment, the plurality of program identifiers
26 identify respective programs recorded by the DVR. In still another embodiment, the STB uses the
27 plurality of program identifiers to display the STB GUI. In yet another embodiment, the STB

1 uses the plurality of program identifiers to demodulate the program data identified by the program
2 identifiers.

3 The present invention may also be regarded as a digital video recorder (DVR) for use with
4 a monitor and a set top box (STB), the STB for demodulating program data from a program
5 signal received over a communication channel and for generating a STB graphical user interface
6 (GUI). The STB further comprises a DVR interface. The DVR comprises a local memory for
7 storing the program data received from the STB, a plurality of program identifiers having
8 information identifying programs to be recorded by the DVR, and a STB interface for
9 communicating with the STB over the DVR interface. The DVR further comprises a DVR
10 controller for receiving from the STB information identifying a program selected by a user from
11 the STB GUI, and for modifying the plurality of program identifiers in response to the information
12 identifying the program selected by the user from the STB GUI.

13 The present invention may also be regarded as a set top box (STB) for use with a monitor
14 and a digital video recorder (DVR), the DVR comprising a STB interface and a plurality of
15 program identifiers. The STB comprising a tuner for demodulating the program data from a
16 program signal received over a communication channel, and a DVR interface for communicating
17 with the DVR over the STB interface. The STB further comprising a STB controller for
18 generating a STB graphical user interface (GUI), for receiving the plurality of program identifiers
19 from the DVR, and for modifying at least one selected operation of the STB in response to the
20 plurality of program identifiers.

21 The present invention may also be regarded as a set top box (STB) for use with a monitor
22 and a digital video recorder (DVR) for storing program data received from the STB. The DVR
23 comprises a STB interface and a plurality of program identifiers having information identifying
24 programs to be recorded by the DVR. The STB comprises a tuner for demodulating the program
25 data from a program signal received over a communication channel, and a DVR interface for
26 communicating with the DVR over the STB interface. The STB further comprises a STB
27 controller for generating a STB GUI and for communicating to the DVR information identifying a

1 program selected by a user from the STB GUI.

2 The present invention may also be regarded as a computer program embodied on a
3 computer readable storage medium for use in a digital video recorder (DVR), the DVR for use
4 with a monitor and a set top box (STB). The STB for demodulating program data from a
5 program signal received over a communication channel and for generating a STB graphical user
6 interface (GUI). The STB comprises a DVR interface and the DVR comprises a STB interface
7 for communicating with the STB over the DVR interface. The DVR comprises a local memory.
8 The computer program comprises code segments for receiving the program data from the STB,
9 and for storing the program data in the local memory. The computer program further comprises
10 code segments for maintaining a plurality of program identifiers, and for communicating to the
11 STB the plurality of program identifiers independent of when the STB demodulates the program
12 data identified by the program identifiers. The STB is responsive to the plurality of program
13 identifiers to modify at least one selected operation of the STB.

14 The present invention may also be regarded as a computer program embodied on a
15 computer readable storage medium for use in a digital video recorder (DVR), the DVR for use
16 with a monitor and a set top box (STB). The STB for demodulating program data from a
17 program signal received over a communication channel and for generating a STB graphical user
18 interface (GUI). The STB comprises a DVR interface and the DVR comprises a STB interface
19 for communicating with the STB over the DVR interface. The DVR comprises a local memory.
20 The computer program comprises code segments for receiving the program data from the STB,
21 and for storing the program data in the local memory. The computer program further comprises
22 code segments for maintaining a plurality of program identifiers, for receiving from the STB
23 information identifying a program selected by a user from the STB GUI, and for modifying the
24 plurality of program identifiers in response to the information identifying the program selected by
25 the user from the STB GUI.

26 The present invention may also be regarded as a computer program embodied on a
27 computer readable storage medium for use in a set top box (STB). The STB for use with a

1 monitor and a digital video recorder (DVR) for storing program data received from the STB. The
2 DVR comprises a STB interface and the STB comprises a DVR interface for communicating with
3 the DVR over the STB interface. The computer program comprises a code segment for
4 demodulating the program data from a program signal received over a communication channel.
5 The computer program further comprises code segments for receiving a plurality of program
6 identifiers from the DVR, and for modifying at least one selected operation of the STB in
7 response to the plurality of program identifiers.

8 The present invention may also be regarded as a computer program embodied on a
9 computer readable storage medium for use in a set top box (STB). The STB for use with a
10 monitor and a digital video recorder (DVR) for storing program data received from the STB. The
11 DVR comprises a STB interface and the STB comprises a DVR interface for communicating with
12 the DVR over the STB interface. The computer program comprises a code segment for
13 demodulating the program data from a program signal received over a communication channel.
14 The computer program further comprises code segments for generating a STB graphical user
15 interface (GUI), and for communicating to the DVR information identifying a program selected
16 by a user from the STB GUI.

17 **BRIEF DESCRIPTION OF THE DRAWINGS**

18 FIG. 1A shows a prior art DVR for use with a STB and a monitor, wherein the user
19 interacts only with the DVR GUI which replaces the STB GUI.

20 FIG. 1B shows a STB and DVR according to an embodiment of the present invention
21 wherein the DVR communicates a plurality of program identifiers to the STB and the STB
22 transmits information to the DVR identifying a program selected by a user from the STB GUI for
23 recording by the DVR.

24 FIGS. 2A and 2B show an embodiment of the present invention wherein a DVR
25 communicates with the STB to coordinate whether the monitor displays the STB GUI or the
26 DVR GUI.

27 FIG. 2C shows a DVR according to an embodiment of the present invention as comprising

1 suitable circuitry for displaying the A/V signal received from the STB (including the STB GUI),
2 or the A/V signal generated internally (including the DVR GUI).

3 FIG. 2D shows an embodiment of the present invention wherein the DVR receives
4 electronic program guide (EPG) data over a dedicated communication channel.

5 FIG. 3A shows an embodiment of the present invention wherein a STB receives
6 commands from a remote control and forwards the commands to the DVR when the DVR GUI is
7 displayed on the monitor.

8 FIG. 3B shows an embodiment of the present invention wherein a DVR receives
9 commands from a remote control and forwards the commands to the STB when the STB GUI is
10 displayed on the monitor.

11 FIG. 4A is a state diagram illustrating an embodiment of the present invention wherein the
12 DVR and STB cooperate to enable user interaction with both the STB menu and the DVR menu.

13 FIG. 4B is a state diagram illustrating an embodiment of the present invention wherein the
14 STB transmits a channel-change event to the DVR whenever the user controls the STB directly to
15 change the tuned channel.

16 FIG. 5 shows an embodiment of the present invention wherein a DVR comprises an A/V
17 file system for storing A/V data.

18 FIG. 6 is a flow diagram according to an embodiment of the present invention wherein the
19 STB receives a list of programs recorded as well as programs scheduled for recording from the
20 DVR and uses the program lists to display EPG data in the STB GUI.

21 FIG. 7A shows an example STB GUI according to an embodiment of the present
22 invention comprising a program guide having indicators of the programs recorded by the DVR as
23 well as programs scheduled for recording by the DVR.

24 FIG. 7B shows an example DVR GUI according to an embodiment of the present
25 invention comprising options for manipulating the DVR and an option for displaying the STB
26 GUI.

27 FIG. 8 shows an example STB GUI according to an embodiment of the present invention

1 comprising an option for displaying the DVR GUI.

2 **DESCRIPTION OF THE PREFERRED EMBODIMENTS**

3 FIG. 1B shows a digital video recorder (DVR) 12 for use with a monitor 14 and a set top
4 box (STB) 16 according to an embodiment of the present. The STB 16 for demodulating
5 program data from a program signal 18 received over a communication channel and for
6 generating a STB graphical user interface (GUI) 20. The STB 16 comprises a DVR interface 34.
7 The DVR 12 comprises a local memory 22 for storing the program data received from the STB
8 16, a plurality of program identifiers, and a STB interface 24 for communicating with the STB
9 over the DVR interface 34. The DVR 12 further comprises a DVR controller 26 for maintaining
10 the plurality of program identifiers, and for communicating to the STB 16 the plurality of program
11 identifiers independent of when the STB 16 demodulates the program data identified by the
12 program identifiers. The STB 16 is responsive to the plurality of program identifiers to modify at
13 least one selected operation of the STB 16.

14 In one embodiment, the plurality of program identifiers identify respective programs
15 scheduled for recording by the DVR 12. In another embodiment, the plurality of program
16 identifiers identify respective programs already recorded by the DVR 12. In one embodiment, the
17 STB 16 uses the plurality of program identifiers to display the STB GUI, and in one embodiment,
18 to display the EPG data. In another embodiment, the STB 16 uses the plurality of program
19 identifiers to demodulate the program data identified by the program identifiers.

20 FIG. 5 shows an embodiment wherein a DVR 51 comprises an A/V file system 53 for
21 storing the A/V data. The STB 16 retrieves the plurality of program identifiers from the DVR 51
22 by accessing the A/V file system 53.

23 In another embodiment, the DVR 12 receives from the STB 16 information identifying a
24 program selected by the user from the STB GUI. The DVR 12 modifies the plurality of program
25 indicators in response to the program selected by the user from the STB GUI.

26 FIG. 6 is a flow diagram illustrating the aforementioned embodiments. At step 62 the
27 system waits until the user selects the option to display the STB GUI. At step 64 the STB 16

1 receives EPG data from a communication channel (e.g., over the same channel as the modulated
2 program data or over a dedicated communication channel). At step 66 the STB 16 receives from
3 the DVR 12 the plurality of program identifiers. At step 68 the STB 16 renders the STB GUI
4 using the EPG data and the plurality of program identifiers received from the DVR 12, and at step
5 70 the STB GUI is displayed on the monitor 14. If at step 72 the user selects a program to record
6 from the STB GUI, then at step 74 the EPG data identifying the selected program is transmitted
7 to the DVR 12 and the DVR 12 updates the plurality of program identifiers so that the selected
8 program will be recorded. Control then loops back to step 66 so that the STB GUI is updated to
9 reflect the user's selection to record the program. The procedure exits when at step 76 the user
10 elects to exit the STB GUI.

11 FIGS. 2A and 2B show a digital video recorder (DVR) 12 for use with a monitor 14 and a
12 set top box (STB) 16 according to another embodiment of the present invention. The STB 16 for
13 demodulating program data from a program signal 18 received over a communication channel and
14 for generating a STB graphical user interface (GUI) 20. The STB further comprises a DVR
15 interface 34. The DVR 12 comprises a local memory 22 for storing the program data received
16 from the STB 16, a STB interface 24 for communicating with the STB 16 over the DVR interface
17 34, and a DVR controller 26. The DVR controller 26 for generating a DVR GUI 28 (FIG. 2B),
18 and in response to user input, communicating with the STB 16 to coordinate whether the monitor
19 14 displays the STB GUI 20 (FIG. 2A) or the DVR GUI 28 (FIG. 2B).

20 In the embodiment of FIGS. 2A and 2B, the STB 16 comprises a tuner 30 for
21 demodulating the program data from the program signal 18, and a STB controller 32 for
22 generating the STB GUI 20 and for communicating with the DVR 12 to coordinate whether the
23 STB GUI 20 or the DVR GUI 28 is displayed on the monitor 14.

24 The STB 16 may be a cable set top box for receiving cable signals, a satellite set top box
25 for receiving satellite signals, or any other similar device for receiving the program signal 18
26 carrying the modulated program data. The program signal 18 may be modulated at any suitable
27 frequency, such as radio or optical frequencies, using any suitable modulation algorithm, such as

1 quadrature amplitude modulation (QAM). The program signal 18 may be demodulated in
2 continuous time wherein the modulated program data is transmitted in analog form, or
3 alternatively, in discrete-time wherein the modulated program data is transmitted in digital form.
4 Further, any suitable compression algorithm may be employed to transmit the modulated program
5 data, such as MPEG encoding.

6 In one embodiment, the DVR interface 24 and STB interface 34 implement a serial
7 communication protocol, such as the Universal Serial Bus (USB) communication protocol.
8 However, the interfaces may implement any suitable digital communication protocol, such as the
9 1394 communication protocol.

10 In the embodiment of FIGs. 2A and 2B, the program data is communicated from the STB
11 16 to the DVR 12 as separate audio and video (A/V) signals 35 which may be analog or digital.
12 In one embodiment, the A/V signal 35 is communicated via a dedicated interface using a separate
13 communication channel, and in an alternative embodiment the A/V signal 35 is communicated via
14 the STB interface 34 and DVR interface 24 over a common communication channel, such as a
15 1394 communication channel, as indicated by the dashed line 36 in FIGs. 2A and 2B.

16 The local memory 22 of the DVR 12 stores the program data (A/V signal 35) in digital
17 form, and in one embodiment, in a compressed form such as MPEG. In one embodiment, the
18 DVR 12 receives the A/V signal 35 in uncompressed form (analog or digital) and comprises
19 suitable circuitry for performing the desired compression before storing the program data in the
20 local memory 22 in compressed form. In an alternative embodiment, the DVR 12 receives the
21 program data in compressed form for storing directly to the local storage 22. In the embodiment
22 of FIGs. 2A and 2B, the DVR 12 further comprises suitable circuitry for decompressing the
23 program data into an internal A/V signal supplied to the monitor 14 during play back.

24 FIG. 2C shows details of suitable circuitry implemented by the DVR 12 according to an
25 embodiment of the present invention. The A/V signal 35 received from the STB 16 is encoded by
26 encoder 21 (e.g., according to the well known MPEG format). The encoded program data 23
27 may be stored by the local storage 22 for playback at a later time. A multiplexer 25 selects

1 between the real-time encoded program data 23 or program data 27 stored by the local memory
2 22, and the selected program data is decoded by decoder 29. The DVR controller 26 comprises
3 an on-screen display module (OSD) 31 for generating the DVR GUI 28 in a layered manner,
4 including an A/V layer comprising the decoded A/V signal 33 output by decoder 29. An adder 41
5 adds the decoded A/V signal 33 with the GUI data output by the OSD 31 to generate an A/V
6 signal 43 representing the DVR GUI 28. A multiplexer 45 selects between the A/V signal 35
7 received from the STB 16, the decoded A/V signal 33 output by decoder 29, and the A/V signal
8 43 representing the DVR GUI 28. The multiplexer 45 outputs the A/V signal 37 supplied to the
9 monitor 14. When the user selects the A/V signal 35 from the STB for display on the monitor 14
10 (including the STB GUI 20), the multiplexer 45 selects the A/V signal 35 received from the STB
11 16. When the user selects the DVR GUI 28 for display on the monitor 14, the multiplexer 45
12 selects the A/V signal 43 representing the DVR GUI 28. When the user selects recorded program
13 data for display on the monitor 14, the multiplexer selects the decoded A/V signal 33 output by
14 the decoder 29. The DVR 12 may continue to record the A/V signal 35 received from STB 16
15 independent of the user's selection as to which A/V signal is displayed on the monitor 14. This
16 enables various trick-play features, such as pausing a real-time program.

17 In one embodiment the STB 16 transmits a control signal to the DVR 12 requesting
18 "focus" of the monitor 14 when the user selects the STB GUI 20 be displayed. In this manner the
19 DVR 12 will select the A/V signal 35 from the STB 16 for display on the monitor 14 rather than
20 the A/V signal 33 or 43 generated internally by the DVR 12.

21 In the embodiment of FIGs. 2A and 2B, the STB 16 receives Electronic Program Guide
22 (EPG) data 38 for use in rendering at least one of the STB GUI 20 and the DVR GUI 28. The
23 EPG data 38 is digital data that may be sent to the STB 16 over a dedicated channel (e.g., over a
24 telephone or cable modem, Ethernet, or other network channel) or over the same channel as the
25 program signal 18 carrying the modulated program data. In one embodiment the EPG data 38 is
26 communicated to the DVR 12 over the STB interface 34 and DVR interface 24. The DVR 12
27 uses the EPG data to render the DVR GUI as described in greater detail in the above referenced

1 patent application entitled "ELECTRONIC PROGRAM GUIDE SUBSYSTEM FOR
2 RECEIVING AND PROCESSING ELECTRONIC PROGRAM GUIDE INFORMATION
3 FROM A SET-TOP BOX". In an alternative embodiment illustrated in FIG. 2D, the DVR 12
4 comprises suitable circuitry for receiving the EPG data over a dedicated communication channel
5 49 (e.g., over a telephone or cable modem, Ethernet, or other network channel).

6 FIG. 3A shows an embodiment of the present invention wherein the STB 16 receives a
7 command representing the user input from a remote control 40 (e.g., via an infrared interface).
8 When the STB GUI 20 is displayed on the monitor 14, the STB 16 processes the command
9 received from the remote control 40, and when the DVR GUI 28 is displayed on the monitor 14,
10 the STB 16 communicates the command received from the remote control 40 to the DVR 12. In
11 an alternative embodiment shown in FIG. 3B, the DVR 12 receives a command representing the
12 user input from a remote control 40. When the DVR GUI 28 is displayed on the monitor 14, the
13 DVR 12 processes the command received from the remote control 40, and when the STB GUI 20
14 is displayed on the monitor 14, the DVR 12 communicates the command received from the
15 remote control 40 to the STB 16.

16 FIG. 4A is a state diagram illustrating an embodiment of the present invention wherein the
17 DVR and STB cooperate to enable user interaction with both the STB GUI and the DVR GUI.
18 When the system is initialized (powered on), the initial state 42 transmits a command to the DVR
19 12 to configure the DVR 12 so that the A/V signal 35 from the STB 16 is displayed on the
20 monitor 14. The system then enters state 44 indicating that the STB 16 has focus of the monitor
21 14. At state 46 the system waits for user input (e.g., from the remote control 40). When user
22 input is received, the system enters state 48 to evaluate the system mode. If the STB 16 currently
23 has focus of the monitor 14, then at state 50 the user input is evaluated to determine whether the
24 user has selected the option to display the DVR GUI. If not, the STB 16 processes the user input
25 at state 52 to perform the appropriate STB function (e.g., change the tuned channel).

26 If at state 50 the user input indicates the user desires the DVR GUI to be displayed, then a
27 command is sent to the DVR 12 so that the A/V signal generated internal to the DVR 12

(including the DVR GUI) is displayed on the monitor 14. That is, focus of the monitor 14 is transferred to the DVR 12 at state 54.

If at state 48 the DVR 12 has focus of the monitor 14, then the user input is communicated from the STB 16 to the DVR 12 for processing. At state 56 the user input is evaluated to determine whether the user has selected the option to display the STB GUI. If not, the DVR 12 processes the user input at state 58 to perform the appropriate DVR function. The system then returns to state 46 to wait for more user input.

If at state 56 the user input indicates the user has selected the option to display the STB GUI, then the DVR 12 is configured to display the A/V signal 35 from the STB 16 and a command is communicated to the STB 16 to display the STB GUI. The system then enters state 44 indicating that the STB 16 has focus of the monitor 14.

FIG. 4B is a state diagram illustrating an embodiment of the present invention wherein the STB 16 transmits a channel-change event to the DVR 12 whenever the user controls the STB 16 directly to change the tuned channel. The state diagram of FIG. 4B is essentially the same as the state diagram of FIG. 4A with an additional state 60 which transmits the channel-change event from the STB 16 to the DVR 12 in connection with the STB 16 changing the tuned channel. In one embodiment, the channel-change event is transmitted to the DVR 12 before the STB 16 actually changes the tuned channel. In this manner, the DVR 12 can warn the user that changing the tuned channel will affect the operation of the DVR 12, allowing the user to abort the operation if desired. In this embodiment, the DVR 12 transmits a control signal to the STB 16 authorizing the STB 16 to change the tuned channel (or abort the operation).

FIG. 7A shows a program guide displayed as part of a STB GUI according to an embodiment of the present invention. The program guide comprises a plurality of program identifiers for identifying programs broadcast on respective channels relative to the time of day (information derived from the EPG data). In addition, the program guide comprises recording indicators for identifying programs that have been recorded and programs scheduled for recording by the DVR 12. In one embodiment, the recording indicators are derived from the program

identifiers received from the DVR 12. Displaying the program guide together with the recording indicators is not limited to the STB GUI; the program guide may be rendered by any suitable video component capable of processing EPG data, such as the DVR 12 or the monitor 14.

In the example of FIG. 7A, the time of day is 9:15pm. The program "Jack and June" has been recorded as indicated by the icon 78 comprising two filled circles. The program "Sports in Review" is currently being recorded as indicated by the icon 80 comprising a filled circle and an empty circle. The program "GO Fast" is scheduled for recording starting at 9:30pm as indicated by the icon 82 comprising two empty circles. This modification enhances the program guide by providing the user with program recording information together with the program guide information. Otherwise the user must exit the program guide and display another menu (e.g., a DVR menu) to view the program recording information which is inconvenient.

FIG. 7B shows an example DVR GUI according to an embodiment of the present invention. The DVR GUI comprises an advertisement 84 and five user selectable options. The "What's on TV" option 86 displays a menu of programs currently being broadcast together with the prerecorded programs in a user preferred format. The "My Recordings" option 88 displays a menu of recorded shows together with EPG data such as the actors, director, and brief synopsis of each program. The "Program Guide" option 90 returns the user to the STB GUI (e.g., the STB GUI of FIG. 7A). The "Select Programs to Record" option 92 displays a menu that enables the user to search for programs to record. For example, the user may search for all "comedy" programs wherein the DVR GUI will display a list of all comedies broadcast over the available channels (as determined from the EPG data). The "Setup" option 94 displays a menu allowing the user to configure the DVR 12 (e.g., display movies in wide-screen or standard format).

FIG. 8 shows a STB GUI according to an alternative embodiment of the present invention. In this embodiment, the STB GUI comprises an option 96 for displaying the DVR GUI (e.g., the DVR GUI of FIG. 7B). In one embodiment, selecting the option 96 from the STB GUI is the only way to access the DVR GUI. In this manner, the user must go through the STB GUI to reach the DVR GUI ensuring that the content of the STB GUI (including advertising content)

1 is always displayed to the user.

2 In another embodiment, the remote control 40 (FIG. 3A or 3B) for generating the user
3 input comprises a first button for selecting the STB GUI to be displayed on the monitor 14 and a
4 second button for selecting the DVR GUI to be displayed on the monitor 14. This embodiment
5 allows the user to quickly switch between the two GUIs by selecting the appropriate buttons on
6 the remote control 40. Referring again to FIG. 3A, when the user presses the button to display
7 the STB GUI, the STB 16 communicates a command to the DVR 12 requesting focus of the
8 monitor 14 so that the DVR will display the A/V signal 35 generated by the STB 16, including the
9 embedded STB GUI. When the user presses the button to display the DVR GUI, the STB 16
10 communicates a command to the DVR 12 directing it to take focus of the monitor 14 by
11 displaying its internal A/V signal (e.g., A/V signal 43 of FIG. 2C), including the embedded DVR
12 GUI.

13 In one embodiment, the DVR 12 executes a computer program embodied on a computer
14 readable storage medium (e.g., local memory 22). The computer program comprises code
15 segments for receiving the program data from the STB 16, and for storing the program data in the
16 local memory 22. The computer program further comprises code segments for maintaining the
17 plurality of program identifiers, and for communicating to the STB 16 the plurality of program
18 identifiers independent of when the STB 16 demodulates the program data identified by the
19 program identifiers. The STB 16 is responsive to the plurality of program identifiers to modify at
20 least one selected operation of the STB 16.

21 In one embodiment, the computer program executed by the DVR 12 comprises code
22 segments for receiving from the STB 16 information identifying a program selected by a user from
23 the STB GUI 20, and for modifying the plurality of program identifiers in response to the
24 information identifying the program selected by the user from the STB GUI 20.

25 In another embodiment, the STB 16 executes a computer program embodied on a
26 computer readable storage medium (e.g., a non-volatile semiconductor memory connected to the
27 STB controller 32). The computer program comprises a code segment for demodulating the

1 program data from a program signal received over a communication channel. The computer
2 program further comprises code segments for receiving the plurality of program identifiers from
3 the DVR 12, and for modifying at least one selected operation of the STB 16 in response to the
4 plurality of program identifiers.

5 In one embodiment the computer program executed by the STB 16 comprises code
6 segments for generating a STB graphical user interface (GUI), and for communicating to the
7 DVR information identifying a program selected by a user from the STB GUI.

100250-0209650